

Version 17.2 replaces Version 17.1 Revision date: 22.08.2018 According to (EU) No. 2015/830

SECTION	1 IDENTIFICATION OF T COMPANY / UNDERTA		/ MIXTURE AND OF THE
1.1	Product identifier:	SPOTCHECK	® SKC-S - aerosol
1.2	Relevant identified uses of the mixture Relevant identified uses:		l against: er used in penetrant
	Uses advised against:		s not recommended for any n the identified uses above.
1.3	Details of the supplier of the safety data Manufacturer: Address: Postcode: Telephone/fax number:	Magnaflux® (+44 (0)1793 524566
	Email address of competent person responsible for SDS: National contact:	support.eu@r	nagnaflux.com
1.4	Emergency telephone number:		ICE HOURS, CALL 3 524566 (English only)
	Opening hours:	Office hours (- 5pm, Friday	GMT) Monday - Thursday 8am 8am - 4pm ICE HOURS, CALL

SECTION 2

HAZARDS IDENTIFICATION

2.1	Classification of the substance or mixture:				
	Classification according to Regulation	Physical and Chemical Hazard:			
	(EC) No 1272/2008 (CLP):	Aerosol 1 H222, H229			
		Health Hazard:			
		Skin Irrit. 2 H315			
		STOT SE 3 H336			

Environmental Hazard: Aquatic Chronic 2 H411 No other information.

Additional information

For full text of hazard statements and EU hazard statements see SECTION 16.

2.2

Label Elements:

Labelling according to regulation (EC) No 1272/2008 [CLP]

Signal Word:	DANGER
Hazard Statement(s):	 H222: Extremely flammable aerosol. H229: Pressurised container: may burst if heated. H315: Causes skin irritation H336: May cause drowsiness or dizziness H411: Toxic to aquatic life with long lasting effects
Precautionary Statement(s):	 P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211: Do not spray on an open flame or other ignition source. P251 Do not pierce of burn even after use. P410 + P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C. P261: Avoid breathing dust/fume/gas/mist/vapours/spray. P280: Wear protective gloves/protective clothing/eye protection/face protection. P501: Dispose of contents/container to hazardous waste or special collection point.
Supplementary Precautionary Statement(s):	P271: Use only outdoors or in a well ventilated area. P302+352: IF ON SKIN: Wash with soap and water P264: Wash thoroughly after handling. P362+P364: Take off contaminated clothing and wash it before reuse.
Supplementary Hazard Information	None
(EU) Hazard Determining Component(s)	Hydrocarbons, C7 – C9, isoalkanes

2.3 Other hazards:

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Vapours can form explosive mixtures with air.

SECTION 3

COMPOSITION / INFORMATION ON INGREDIENTS

3.2 Mixtures

Ingredient Name	CAS No	EC No	REACH Registration Number	% Weight	Classification according to Regulation (EC) No 1272/2008 [CLP]	Additional information
Hydrocarbons, C7- C9, isoalkanes		921- 728-3	01- 2119471305- 42	60 -100	Flam. Liq 2: H225 Skin Irrit. 2: H315 STOT SE3: H336 Asp. Tox. 1: H304 (note1) Aquatic Chronic 2: H411	No other information
Hydrocarbons, C3-4-rich petroleum distillate petroleum gas (1.3 butadiene < 0.1%)	68512- 91-4	270- 990-9	(note2)	10-30	Press. Gas H280 Flam. Gas 1 H220	(note3)
 Mixtures classified as Asp. Tox. 1 H304 need not be labelled when placed on the market in aerosol containers or in containers fitted with a sealed stray attachment. 						

containers fitted with a sealed spray attachment.
 Exempted from the obligation to register in accordance with art.2(7)(a) of REACH Regulation No 1907/2006

Not classified as carcinogen, less than 0.1% w/w 1,3 butadiene (EINECS no 203-450-8)

Note: Hazard statement(s) in this section apply only to raw materials, not necessarily to finished products.

*See Section 16 for hazard statement(s) text in full.

SECTI	ON 4 FIRST AID MEASU	IRES
4.1	Description of first aid measures: General notes:	If symptoms persist, seek medical attention. Show this safety data sheet to the doctor in attendance.
	Following inhalation:	Remove to fresh air. Keep at rest. If not breathing give artificial respiration. Seek prompt medical attention if discomfort persists.
	Following skin contact:	Flush with water, use soap if available. Contaminated clothing should be washed before re-use. Seek medical attention if irritation persists.
	Following eye contact:	Flush eyes with large amounts of water for at least 15 minutes with eyelids held open. Seek medical attention if irritation persists.
	Following ingestion:	Unlikely route of exposure. Rinse mouth with water. Do NOT induce vomiting. If vomiting occurs, keep head low so that stomach contents don't enter the lungs. Never give anything by mouth to an unconscious person. Seek medical
	Self-protection of the first aider:	attention immediately. No action shall be taken involving any personal risk or without suitable training. If it is suspected that the mixture is still present, wear appropriate personal protective equipment.

4.2 Most important symptoms, both acute and delayed:

Prolonged skin contact may cause redness and irritation.
 In high concentrations, vapours are anaesthetic and may cause headache, fatigue, dizziness and central nervous system effects.
 Fumes from the stomach contents may be inhaled resulting in the same symptoms as inhalation. Avoid vomiting and normal rinse of stomach because of risk of aspiration. May cause discomfort to the eyes. Symptoms: redness and pain.
 Indication of any immediate medical attention and special treatment needed: None known.

SECTI	ON 5 FIREFIGHTING MEAS	URES
5.1	Extinguishing media:	
	Suitable extinguishing media:	Carbon dioxide, foam, dry chemical, water fog or spray.
	Unsuitable extinguishing media:	Do not use water jet.
5.2	Special hazards arising from the	Evacuate immediate area. Shut off 'fuel' to
	substance or mixture:	fire. If possible keep unaffected containers cool with water spray.
		Aerosols may explode in a fire.
		Aerosol contents are extremely flammable.
	Hazardous combustion products:	Smoke, soot and oxides of carbon. Burning
		vapour may give off toxic fumes.
5.3	Advice for fire-fighter:	
	Warn firefighters that aerosols are involve protective clothing must be worn. Water s Contaminated extinguishing water must b regulations.	
SECTI	ON 6 ACCIDENTAL RELEAS	SE MEASURES
6.1	Personal precautions, protective equip	
	Suitable protective equipment (see Section contamination of skin, eyes and personal	clothing.
	For non-emergency personnel:	Remove ignition sources. Avoid breathing vapours, mist or gas.
	For emergency responders:	Remove ignition sources. Avoid breathing vapours, mist or gas. Keep unnecessary

6.2 **Environmental precautions:**

Prevent liquid from entering drains, sewers and watercourses. Notify the Environment Agency or water authorities if a major spillage occurs.

6.3 Methods and material for containment and cleaning up:

Eliminate sources of ignition. Take measures to prevent the build-up of electrostatic charge.

Avoid breathing vapours. Ventilate surrounding area.

For containment:

Contain spillage, and then collect with noncombustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite). Place in a UN approved container for disposal.

people at a safe distance.

Large spills should be pumped (using an earthed explosion proof pump) into UN approved containers pending disposal. Dispose of waste according to local/national regulations.

Do not flush away residues with water. No other information.

For cleaning up: Other information:

6.4

Reference to other sections:

For Personal Protective Equipment see Section 8. For disposal information see Section 13.

SECTION	N 7 HANDLING & STORAGE	
7.1	Precautions for safer handling: Protective Measures:	Wear suitable protective clothing such as chemical resistant gloves, apron and goggles/face mask to protect from splashes. Ensure adequate exhaust ventilation when in use. Avoid contact with skin and eyes. Do not breathe product spray or mist. Risk of vapour concentration in low areas.
	Measures to prevent fire: Advice on general occupational	Aerosol contents are highly flammable and volatile. Keep away from sources of ignition – no smoking. Take measures to prevent the build-up of electrostatic charge. Equipment should be earthed. Use explosion proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Wash thoroughly after handling.
	hygiene:	
7.2	Conditions for safe storage, including any Technical measures and storage conditions: Packaging materials:	/ incompatibilities: Store in a cool dry area away from heat and sources of ignition. Store in original container.
	Requirements for storage rooms and vessels:	Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Recommended storage temperature 10 °C to 30 °C.
7.3	Further information on storage conditions: Specific end use(s):	Rotate stock and check regularly for damaged items.
	Recommendations:	Use only for Non Destructive Testing (NDT) applications.
	Industrial sector specific solutions:	See product data sheet for further information.

SECTION 8

EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters:

Occupational exposure limit values:

Occupational exposure figures have been set for some of the components of this preparation based on GESTIS International Limit Values or manufacturers' recommendation.

		Limit value - 8 hours		Limit value - short term	
Ingredient name	Country	ppm	mg /m³	ppm	mg /m ³
Hydrocarbons, C7 – C9, isoalkanes	UK	241	1200		
Data obtained from GESTIS International Limit Values, EH40, supplier's SDS					

Note: Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.

Derived No Effect Level (DNEL) - Hydrocarbons, C7 - C9, isoalkanes

End User	Exposure Route	Exposure Time	Effects	DNEL
Worker	Inhalation	Long term	Systemic	2035 mg/m ³
Worker	Dermal	Long term	Systemic	773 mg/kg bw/day

Note: The Derived No Effect Level (DNEL) is an estimated safe level of exposure that is derived from toxicity data in accordance with specific guidance within the European REACH regulation. The DNEL may differ from an Occupational Exposure Limit (OEL) for the same chemical. OELs may be recommended by an individual company, a government regulatory body or an expert organization, such as the Scientific Committee for Occupational Exposure Limits (SCOEL) or the American Conference of Governmental Industrial Hygenists (ACGIH). OELs are considered to be safe exposure levels for a typical worker in an occupational setting for an 8-hour work shift, 40 hour work week, as a time weighted average (TWA) or a 15 minute short-term exposure limit (STEL). While also considered to be protective of health, OELs are derived by a process different from that of REACH.

Predicted No Effect Concentration (PNEC) - Hydrocarbons, C7 - C9, isoalkanes

Water - Fresh Water	No data available: testing technically not feasible
Water - Marine Water	No data available: testing technically not feasible
Water - Intermittent release	No data available: testing technically not feasible
Sediment - Fresh water	No data available: testing technically not feasible
Sediment - Marine water	No data available: testing technically not feasible
Soil	No data available: testing technically not feasible
Sewage Treatment plant	No data available: testing technically not feasible

8.2 Exposure controls:

Concentrations of product vapours and mists in the working atmosphere must be kept as low as is reasonably practicable. Exposure should be minimised by the use of appropriate containment, engineering control and ventilation measures. Where this is not possible, personal protective equipment should be worn as indicated below where appropriate.

Appropriate engineering controls:	Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limits are not exceeded
Personal protection equipment: Eye and face protection:	Safety glasses with side-shields conforming to EN166.
Skin protection - hand:	 Protective gloves conforming to EN374-3. Use chemical resistant gloves recommended by glove manufacturer as being suitable for isoparaffins, if hand exposure is unavoidable. Protective gloves made of nitrile rubber are suitable, although other types may be more suitable in other circumstances. For prolonged exposure, recommended gloves with protective index 6, > 480 minutes permeation time according to EN374.
Skin protection – other:	Consult the glove manufacturer for exact breakthrough time. Glove manufacturer's directions for use should be observed. Wear impervious, flame retardant antistatic protective clothing. The type of
	arrotative protocorrot distance. The type of protective equipment must be selected according to the concentration and amount of dangerous substance at the specific workplace.

	Respiratory protection:	In case of insufficient ventilation, wear suitable respiratory equipment. Filter type A. (EN 136, 140, 405, 149, 143) For higher level protection use type ABEK-P3 (EU EN 143) respirator cartridges. Use respirators and components tested and approved under CEN standards.
	Thermal hazards:	Not applicable.
	Environmental exposure controls:	Avoid any release to the environment.
SECTION	N 9 PHYSICAL & CHEMICAL F	PROPERTIES
9.1	Information on basic physical and chemical Appearance: Odour: Odour threshold: pH: Melting point/freezing point: Initial boiling point and boiling range: Flash point (PMCC): Evaporation rate (BuAc = 100): Flammability (solid, gas) (Limits in air): Upper/lower flammability or explosive limits: Vapour pressure: Vapour pressure: Vapour density (Air = 1): Relative density: Solubility: Partition coefficient: n-octanol/water: Auto-ignition temperature: Decomposition temperature: Viscosity (ASTM D445): Explosive properties:	A properties: Aerosol containing mobile clear liquid. Mild hydrocarbon. No data available. Neutral. No data available. $113 - 143 ^{\circ}$ C. $-40 ^{\circ}$ C (aerosol propellant). 155. No data available. 0.7 - 6.0% (Vol%) 1.627 kPa @ 20 $^{\circ}$ C. > 1. $0.72 ^{\circ}$ g/cm ³ . Insoluble. No data available. > 200 $^{\circ}$ C. No data available. $0.86 ^{\circ}$ mm ² /s @ 25 $^{\circ}$ C. Under normal conditions no danger of explosion. No data available.

Note: properties relate to the bulk product only unless otherwise stated.

9.2 Other information: No other information.

SECTIO	ON 10 STABILITY & REACTIV	ТҮ
10.1	Reactivity:	No specific reactivity hazards associated with this product.
10.2	Chemical stability	Stable under normal conditions of use and applications.
10.3	Possibility of hazardous reactions:	No data available.
10.4	Conditions to avoid:	Keep away from sources of ignition, hot surfaces and direct sun light.
10.5	Incompatible materials:	Strong oxidising agents.
10.6	Hazardous decomposition materials:	None under normal conditions of use. Smoke, soot and oxides of carbon on combustion.

1

SECTION 11 TOXICOLOGICAL INFORMATION			
11.1	Information on toxicological effects: based on data for component materials.		
	Acute toxicity - oral:	Based on the available data, the classification criteria	
	Acute toxicity – dermal:	are not met. Based on the available data, the classification criteria are not met.	
	Acute toxicity – inhalation:	Based on the available data, the classification criteria are not met.	
	Skin corrosion/irritation:	Skin Irrit. 2 H315: Causes skin irritation.	
	Serious eye damage/irritation:	Based on the available data, the classification criteria are not met.	
	Respiratory sensitisation:	Data lacking.	
	Skin sensitisation:	Based on the available data, the classification criteria are not met.	
	Germ cell mutagenicity:	Based on the available data, the classification criteria are not met.	
	Carcinogencity:	Data lacking.	
	Reproductive toxicity:	Based on the available data, the classification criteria are not met.	
	STOT single exposure:	STOT Single Exp. 3 H336: May cause drowsiness or dizziness. Affected organs: central nervous system	
	STOT repeated exposure:	Route of exposure: inhalation Based on the available data, the classification criteria are not met.	
	Aspiration hazard:	Mixtures from Aerosol Dispensors - need not be classified as Asp. Tox. 1 - H304 as the aerosol spray is fine and a pool of product may not be formed in the mouth.	
		xposure and Potential Health Effects:	
	Inhalation:	Vapour concentrations above the recommended exposure levels are irritating to the eyes and respiratory tract, may cause headaches and dizziness, are anaesthetic and may have other central nervous system effects.	
	Ingestion:	Not a likely route of exposure. However, harmful: May cause lung damage if swallowed. Ingestion may cause irritation of the mouth, throat and digestive tract. Small amounts of product aspirated into the respiratory system during ingestion or from vomiting may cause bronchopneumonia or pulmonary edema.	
	Eye contact: Skin contact:	May cause redness and pain. Frequent or prolonged contact with the product may produce irritation and/or skin dryness and cracking. Product will have a de-fatting effect on the skin.	
	Toxicity Test Results: based on o	data for component materials, where available.	

1

Hydrocarbons, C7 – C9, isoalkanes

Acute Toxicity – oral	LD50 (rat)	> 5000 mg/kg
Acute Toxicity – dermal	LD50 (rabbit)	> 2000 mg/kg
Acute Toxicity – inhalation	LC50 (rat)	21 mg/l (4 h; vapour)

Other Information:

No other information.

SECTION 12

ECOLOGICAL INFORMATION

Based on data for component materials 12.1 Toxicity:

Fish		Oncorhynchus mykiss	Oncorhynchus mykiss		96h	18.4 mg/l
Aquatic I	nvertebrates	Daphnia magna		EL50	48h	2.4 mg/l
Aquatic F	Plants	Pseudokirchneriella subcapit	tata	EL50	72h	29 mg/l
12.2	Persistence and degradability:			Hydrocarbons, C7 – C9, isoalkanes - Biodegradable.		
12.3	Bioaccumula	ative potential:	No data	available.		
	(log Kow):	efficient: n-octanol/water ation factor (BCF):		available. available.		
12.4	Mobility in s	oil:	spread c	on the wate	er surface.	th water and will Product is
12.5	Results of PBT and vPvB assessment:		highly volatile - will partition rapidly to air. This mixture does not contain any substances that are assessed to be a PBT or vPvB.			
12.6	Other advers	se effects:	No data	available.		

13.1 Waste treatment methods:

Dispose of waste and residues in accordance with local authority requirements. Seek the advice of an approved waste disposal contractor for disposal at a licensed facility in accordance with national legislation.

Product/packing disposal:	Empty containers may contain residual
	product and flammable vapours. Do not
	pierce or burn container, even after use.
	Do NOT remove labels. Keep away from
	sources of ignition.
Waste codes/waste designations	16 05 04* gases in pressure containers
according to LoW:	containing dangerous substances.

NOTE: Waste codes are assigned based upon the most common uses for this material and may not reflect contaminants resulting from actual use. Waste producers need to assess the actual process used when generating the waste and its contaminants in order to assign the proper waste code(s).

Waste treatment – relevant information:	Dispose of waste and residues in accordance with local authority requirements. Seek the advice of an approved waste disposal contractor for disposal at a licensed facility in accordance with national legislation
Sewage disposal – relevant information:	Do not empty down the drain.
Other disposal recommendations:	Use a licensed waste contractor

SECTION 14 TRANSPORT INFORMATION				
14.1	UN number:		ADR/RID: IMDG:	UN1950 UN1950
14.2	UN proper shipping name:		IATA: ADR/RID: IMDG: IATA:	UN1950 AEROSOLS, flammable AEROSOLS, flammable AEROSOLS, flammable
14.3	Transport hazard class(es)	:	ADR/RID: IMDG: IATA:	2.1 2.1 2.1
14.4	Packing group:		ADR/RID: IMDG: IATA:	N/A N/A N/A
14.5	Environmental hazards:		ADR/RID: IMDG: IATA:	Yes Marine Pollutant: Yes Yes
14.6	Special precautions for use ADR/RID – Tunnel code: IMDG – Ems: IATA/ICAO – PAX: IATA/ICAO – CAO:	er: (D) F-D, S-U 203 203		
14.7	Transport in bulk according Not applicable	g to Annex II o	f Marpol 73/78	and the IBC code:

SECTION 15	REGULATORY INFORMATION	
------------	------------------------	--

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

EU Regulations:

This data sheet complies with the requirements of Regulation (EC) No 1272/2008 on the classification, labelling and packaging of substances and mixtures.

Safety data sheet as required by EC-Regulations 1907/2006 and REACH Annex II Amendment (EU) No. 2015/830.

Information according to 2013/10/EU and 2008/47/EC amendment of the aerosol directive 75/324/EEC.

This data sheet is complied according Dir 2013/10/EU, 2008/47/EEC amendment of the aerosol directive 75/324/EEC.

Extra label elements: Pressured container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material.

Mixtures classified as Asp. Tox. 1 H304 need not be labelled when placed on the market in aerosol containers or in containers fitted with a sealed spray attachment.

National regulations (Germany):
Wassergefahrdungklasse (water
hazard class):
TechnischeAnleitungLuft (TA-Luft):

WGK 2 - Hazard to waters.

Class 5.2.5 Organic Substances, except dusts

15.2 Chemical safety assessment: No data available

SEC	TION 16	OTHER INFORMATION
(i)	Indication o	of changes: 2 updated in Section 1.3.
	Vertical lines	s on the left hand side indicate an amendment from the previous version.
(ii)		ns and acronyms:
	ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road (Accord européen relatif au transport international des marchandises Dangereuses par Route)
	CAS No.	Chemical Abstracts Service number
	CEN	European Committee for Standardisation
	CLP ECHA	Classification, Labelling Packaging Regulation; Regulation (EC) No 1272/2008 European Chemicals Agency
	EC50	Half Maximal Effective Concentration
	EC number	EINECS and ELINCS number
	EINECS	European Inventory of Existing Commercial Substances
	ELINCS	European List of notified Chemical Substances
	GHS	Globally Harmonized System
	IATA IMDG	International Air Transport Association International Maritime Dangerous Goods
	LC50	Lethal Concentration to 50% of a test population
	LD50	Lethal Dose to 50% of a test population
	MPI	Magnetic Particle Inspection
	NDT	Non-Destructive Testing
	OEL PBT	Occupational Exposure Limit Persistent, Bioaccumulative and Toxic Substance
	PMCC	Pensky-Martens closed cup method
	PPE	Personal Protection Equipment
	REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation EC (No) 1907/2006
	RID	Regulations concerning the International Carriage of Dangerous Goods by Rail (Reglement International concernant le transport des marchandises Dangereuses par chemin de fer)
	SDS	Safety Data Sheet
	STOT RE	Specific Target Organ Toxicity, Repeat Exposure
	STOT SE TA-Luft	Specific Target Organ Toxicity, Single Exposure Technical Instructions on Air Quality Control (Technische Anleitung zur
		Reinhaltung der Luft)
	vPvB	Very Persistent and Very Bioaccumulative
	WEL	Workplace Exposure Limit
<i>/</i> ····	WGK	German Water Hazard Class (Wassergefährdungsklasse)
(iii)	Key lite	erature and sources of data:
	•	Supplier's safety data sheets for components listed in Section 3. European Chemicals Agency, <u>http://echa.europa.eu/</u>
	•	GESTIS International Limit Values Database,
		http://limitvalue.ifa.dguv.de/Webform_gw.aspx
	•	Occupational Exposure Limits EH40/2005.
	•	Commission regulation (EU) 2015/830.
	•	Control of Substances Hazardous to Health Regulations 2002.
	•	Hazardous waste regulations 2005.
	•	Health & Safety at Work Act 1974. Regulation (EC) No. 1907/2006 (REACH).
	•	Regulation (EC) No. 1907/2006 (REACH). Regulation (EC) No. 1272/2008 (CLP).
	-	

(iv) Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 (CLP):

Classification according to Regulation (EC) No 1272/2008	Classification procedure
Aerosol. 1: H222, H229	Test Method
Skin Irrit. 2: H315	Calculation Method
STOT SE3: H336:	Calculation Method
Aquatic Chronic 2: H411	Calculation Method

(v) Hazard statements (number and full text):

H220: Extremely flammable gas.

H225: Highly flammable liquid and vapour

H222: Extremely flammable aerosol.

H229: Pressurised container: may explode if heated.

H280: Contains gas under pressure; may burst if heated.

H304: May be fatal if swallowed and enters airways

H315: Causes skin irritation

H336: May cause drowsiness or dizziness

H411: Toxic to aquatic life with long lasting effects

Hazard Class and Category Code (full text):

Aerosol 1: Aerosol

Aquatic Chronic 2: Hazardous to the aquatic environment

Asp. Tox. 1: Aspiration hazard

Flam. Gas 1: Flammable Gas

Flam. Liq. 2: Flammable liquid

Press. Gas: Gases under pressure

Skin Irrit. 2: Skin corrosion/irritation

STOT SE 3: Specific target organ toxicity - single exposure

Relevant precautionary statements (number and full text):

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251 Do not pierce of burn even after use.

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.

P271: Use only outdoors or in a well ventilated area.

P410 + P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

P280: Wear protective gloves/protective clothing/eye protection/face protection

P302+352: IF ON SKIN: Wash with soap and water

P362+P364: Take off contaminated clothing and wash it before reuse.

P264: Wash thoroughly after handling.

P501: Dispose of contents/container to hazardous waste or special collection point.

(vi) Training advice:

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene. Chemical hazard risk assessment. Provide adequate information, instruction and training to operators.

DISCLAIMER

The information and recommendations contained herein are based upon data believed to be up-todate and correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information and recommendations contained herein. We accept no responsibility and disclaim all liability for any harmful effects that may be caused by (incorrect) use, handling, purchase, resale, or exposure to our product. Customers and users of our product must comply with all applicable health and safety laws, regulations, and orders. In particular, they are under an obligation to carry out a risk assessment for the particular work places and to take adequate risk management measures in accordance with the national implementation legislation of EU Directives 89/391/EEC and 98/24/EC amended by Directive 2014/27/EU.

Revision summary:	Revision Comments	This SDS is valid from the Revision Date. If you require a SDS for the product manufactured before the Revision Date please contact us at support.eu@magnaflux.com.
	Revision Date Version	22.08.2018 17.2